

Temperature Performance Eppendorf ThermoStat™ C with individual Eppendorf SmartBlocks

With the new generation of the Eppendorf ThermoStat individual data regarding the temperature performance are available for each Eppendorf SmartBlock. Detailed specifications are listed below:

Eppendorf ThermoStat™ C with Eppendorf SmartBlock

	0.5 ml	1.5 ml	2.0 ml	cryo	12 mm	PCR 96	PCR 384	Plates	5 ml	15 ml	50 ml
Minimum temperature below ambient temperature	max. 28 °C			max. 27 °C		max. 30 °C		max. 27 °C		max. 22 °C	max. 23 °C
Max. temperature accuracy 20–45 °C	+/- 0.5 °C				+/- 1 °C						
Max. temperature accuracy <20 °C and >45 °C	+/- 1 °C				+/- 3 °C		+/- 2 °C				
Max. temperature homogeneity 20–45 °C						+/- 0.5 °C					
Max. homogeneity <20°C or >45°C	+/- 1 °C				+/- 2 °C						
Max. heating rate (in °C/min)	7.5 °C	6.5 °C	7 °C	7.5 °C	7 °C	7 °C	9 °C	8.5 °C	6.5 °C	4.5 °C	4.5 °C
Max. cooling rate above ambient temperature (in °C/min)	5.5 °C	5 °C		5.5 °C		4.5 °C	5.5 °C	6 °C	4.5 °C	3.5 °C	4 °C
Max. cooling rate below ambient temperature (in °C/min)				2.5 °C		3 °C		2 °C		1.5 °C	

Your local distributor: www.eppendorf.com/contact
 Eppendorf AG · 22331 Hamburg · Germany
eppendorf@eppendorf.com · www.eppendorf.com

www.eppendorf.com

Eppendorf®, and the Eppendorf logo are registered trademarks of Eppendorf AG, Hamburg.
 Eppendorf ThermoStat™ C and Eppendorf SmartBlock™ are trademarks of Eppendorf AG, Hamburg.
 All rights reserved, including graphics and images. Copyright © 2013 by Eppendorf AG.