

# 73-847

Neoprene Exam Glove with ERGOFORM Ergonomic Design Technology



# Ergonomically designed with exceptional grip

- Designed with ERGOFORM<sup>™</sup> Technology to support musculoskeletal health and increase worker productivity
- · Certified for exceptional wet grip



#### **Industries**

Life Sciences

#### **Recommended For**

- Plant disinfection and sanitization
- Maintaining lab furniture and equipment
- Transferring liquids and solids
- Transferring liquids
- Loading centrifuges and chromatography columns
- Assembly of parts
- Sample taking and processing
- Blending, compounding solids and liquids
- Raw material sample collection
- Enhanced grip in wet environments
- Extra comfort during long, sustained procedures
- Damp donning







# 73-847

**Neoprene Exam Glove with ERGOFORM Ergonomic Design Technology** 

#### **TECHNICAL DATA SHEET**

#### **PRODUCT INFORMATION**

Color Gree Glove Design Poly Cuff Beac	prene (Polychloroprene) en vmer Coated, Powder-Free, Textured Fingers ded
Color Gree Glove Design Poly Cuff Beac	rmer Coated, Powder-Free, Textured Fingers ded
Glove Design Poly Cuff Beac	mer Coated, Powder-Free, Textured Fingers ded
Cuff Bead	ded
Manufacturing/OMS	
Manufacturing/QMS	
Audit Standards	13485:2003
	M D6977, Category III, EN 374:2003, EN ISO 374-1:2016, EN 420:2003 + A1:2009, EN ISO 374- 016, EN 421:2010
Packaging 100	gloves per dispenser 10 dispensers per case 1000 gloves per case
<b>Storage</b> Keep	p out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
Country of Origin Indo	pnesia
User Needs Segment Mult	zi-Purpose
Available sizes XS (	(5.5 - 6), S (6.5 - 7), M (7.5 - 8), L (8.5 - 9), XL (9.5 - 10)
Anti-static No	
Accelerators	nc Dibutyldithiocarbamate (ZDBC)  a very small number of users may be sensitive to this ingredient(s) and hence may develop irritant and/or allergic act reactions.

#### **PHYSICAL PROPERTIES**

	Typical	<b>Testing Method</b>	
Length (mm/inches)	245 /	ASTM D3767,EN 420	
Freedom from Holes (Inspection level I)	1.5 AQL		ASTM D5151,EN 455-1
Palm Thickness (mm/mils)	0.10 / 3.9		ASTM D3767,EN 420
Finger Thickness (mm/mils)	0.13 / 5.1		ASTM D3767,EN 420
	<b>BEFORE AGING</b>	AFTER AGING	
Ultimate Tensile Strength (MPa)	≥ 18	≥ 14	ASTM D412 & D573
Elongation at Break (%)	≥ 500	≥ 400	ASTM D412
Force at break (N)	<6	<6	

#### **ORDERING INFORMATION**

Size	XS (5.5 - 6)	S (6.5 - 7)	M (7.5 - 8)	L (8.5 - 9)	XL (9.5 - 10)
Product Code	73847060	73847070	73847080	73847090	73847100

#### **Technology**



### For additional information visit us at www.ansell.com, or call us at

#### Europe, Middle East & Africa Region

Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

#### Asia Pacific Region

Ansell Global Trading Center (Malaysia) Sdn Bhd T: +603 8310 6688 F: +603 8310 6699

#### North America Region

Ansell Healthcare Products LLC T: +1800 800 0444 F: +1800 800 0445

## Latin America & Caribbean Region

Ansell Commercial Mexico S.A. de C.V. T: +52 442 248 1544 / 248 3133

#### Australia

Ansell Limited T: +61 1800 337 041 F: +61 1800 803 578

### Russia

Ansell PYC Ten. +7 495 258 13 16

#### **Performance Standards and Regulatory Compliance**











Ansell,  $^{\circledR}$  and  $^{\intercal}$  are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking  $^{\circledR}$  2020 Ansell Limited. All Rights Reserved.



