

SLS Lab Pro Unstirred Water Baths

SLS Lab Pro Unstirred Water Baths

The SLS Lab Pro Range of Unstirred Water Baths 2-28L provide class leading performance and reliability for scientific, laboratory and industrial applications for consistent temperature control.



- PID temperature control, increments 0.1°C
- Bold LED temperature display
- Stainless steel tank with concealed heaters and sensors
- Painted surfaces feature antibacterial finish
- Safety features, thermal cut out and over temperature alarm protecting lab work/samples
- Factory temperature calibration, fully tested
- Accessories available, enquire for details
- Lid included



SLS1178



SLS1180



SLS1176

Standard specification	
Construction	Stainless steel 304 spec tank. Painted surfaces feature "anti-bacterial technology".
Temperature range, °C	Ambient +5 to 99, PID digital LED display showing actual or set temperature, resolution 0.1°C
Stability, °C	±0.2
Safety	Over temperature thermal cut out.
Voltage, V	230
Warranty, years	3

	Overall Dims w x d x h, mm	Tank Dims w x d x h, mm	Tank max capacity, L	Energy use, kWh	Drain	Packed size, cm/Weight, kg w x d x h, cm/kg
SLS1274	332 x 185 x 135	300 x 150 x 65	2	0.2 @ 37°C	No	30 x 23 x 29/ 5.5
SLS1176	332 x 185 x 290	300 x 150 x 150	4	0.2 @ 37°C	No	30 x 23 x 29/ 5.5
SLS1178	361 x 332 x 290	325 x 300 x 150	14	0.4 @ 37°C	No	45 x 41 x 32/ 8
SLS1180	538 x 332 x 290	500 x 300 x 150	22	0.55 @ 37°C	Yes	62 x 41 x 37/ 11
SLS1181	538 x 332 x 290	500 x 300 x 200	28	0.55 @ 37°C	Yes	62 x 41 x 37/ 11